

## 4 發展項目的設計的資料 INFORMATION ON DESIGN OF THE DEVELOPMENT

發展項目將會有構成圍封牆的一部分的非結構的預製外牆。

There will be non-structural prefabricated external walls forming part of the enclosing walls of the development.

每幢建築物的非結構的預製外牆的厚度範圍為150毫米。

The range of thickness of the non-structural prefabricated external walls of each block is 150mm.

發展項目將會有構成圍封牆一部分的幕牆。

There will be curtain walls forming part of the enclosing walls of the development.

每幢建築物的幕牆的厚度範圍為200毫米。

The range of thickness of the curtain walls of each building is 200mm.

每個住宅物業的非結構的預製外牆及幕牆的總面積表

SCHEDULE OF TOTAL AREA OF THE NON-STRUCTURAL PREFABRICATED EXTERNAL WALLS AND CURTAIN WALLS OF EACH RESIDENTIAL PROPERTY

樓層 Floor	單位 Flat	每個住宅物業的非結構的預製外牆的總面積 (平方米) The total area of the non-structural prefabricated external walls of each residential property (sq.m.)	每個住宅物業的幕牆的總面積 (平方米) The total area of the curtain walls of each residential property (sq.m.)
2樓至3樓及 5樓至12樓 2/F-3/F and 5/F-12/F	A1	0.338	-
	A2	-	0.985
	A3	-	-
	A5	-	0.985
	A6	0.338	-
	B1	0.863	-
	B2	-	0.980
	B3	-	-
	B5	-	0.980
	B6	0.863	-
15樓至23樓 15/F-23/F	A1	0.338	-
	A2	0.413	0.985
	A3	-	0.985
	A5	0.338	-
	B1	0.863	-
	B2	0.413	0.980
	B3	-	0.980
	B5	0.863	-